

# SQL Practice 1

One table, Aggregation, Group By  
24 Queries

Database: DBSQLPractice.sql

Source Link: <https://www.w3resource.com/sql-exercises/>

**salesman**

<u>salesman_id</u>	<u>name</u>	<u>city</u>	<u>commission</u>
5001	James Hoog	New York	0.15
5002	Nail Knite	Paris	0.13
5005	Pit Alex	London	0.11
5006	Mc Lyon	Paris	0.14
5003	Lauson Hen		0.12
5007	Paul Adam	Rome	0.13

**customer**

<u>customer_id</u>	<u>customer_name</u>	<u>city</u>	<u>grade</u>	<u>salesman_id</u>
3002	Nick Rimando	New York	100	5001
3005	Graham Zusi	California	200	5002
3001	Brad Guzan	London		
3004	Fabian Johns	Paris	300	5006
3007	Brad Davis	New York	200	5001
3009	Geoff Camero	Berlin	100	
3008	Julian Green	London	300	5002
3003	Jozy Altidor	Moncow	200	5007

<u>order no</u>	<u>purch amt</u>	<u>order date</u>	<u>customer id</u>	<u>salesman id</u>
70001	150.5	2016-10-05	3005	5002
70009	270.65	2016-09-10	3001	
70002	65.26	2016-10-05	3002	5001
70004	110.5	2016-08-17	3009	
70007	948.5	2016-09-10	3005	5002
70005	2400.6	2016-07-27	3007	5001
70008	5760	2016-09-10	3002	5001
70010	1983.43	2016-10-10	3004	5006
70003	2480.4	2016-10-10	3009	
70012	250.45	2016-06-27	3008	5002
70011	75.29	2016-08-17	3003	5007

# Query 1

- Display name and commission for all the salesmen.

*salesman (salesman\_id, name, city, commission)*

<u>name</u>	<u>commission</u>
James Hoog	0.15
Nail Knite	0.13
Pit Alex	0.11
Mc Lyon	0.14
Paul Adam	0.13
Lauson Hen	0.12

```
SELECT name, commission  
FROM salesman;
```

salesman_id	name	city	commission
5001	James Hoog	New York	0.15
5002	Nail Knite	Paris	0.13
5005	Pit Alex	London	0.11
5006	Mc Lyon	Paris	0.14
5003	Lauson Hense		0.12
5007	Paul Adam	Rome	0.13

```
SELECT name, commission  
FROM salesman;
```

salesman_id	name	city	commission
5001	James Hoog	New York	0.15
5002	Nail Knite	Paris	0.13
5005	Pit Alex	London	0.11
5006	Mc Lyon	Paris	0.14
5003	Lauson Hense		0.12
5007	Paul Adam	Rome	0.13

# Query 2

- Retrieve salesman id of all salesmen from orders table without any repeats.

*orders(ord\_no, purch\_amt, ord\_date, customer\_id, salesman\_id)*


<u>salesman_id</u>
5002
5003
5006
5001
5005
5007

```
SELECT DISTINCT salesman_id  
FROM orders;
```

ord_no	purch_amt	ord_date	customer_id	salesman_id
70001	150.50	2012-10-05	3005	5002
70009	270.65	2012-09-10	3001	5005
70002	65.26	2012-10-05	3002	5001
70004	110.50	2012-08-17	3009	5003
70007	948.50	2012-09-10	3005	5002
70005	2400.60	2012-07-27	3007	5001
70008	5760.00	2012-09-10	3002	5001
70010	1983.43	2012-10-10	3004	5006
70003	2480.40	2012-10-10	3009	5003
70012	250.45	2012-06-27	3008	5002
70011	75.29	2012-08-17	3003	5007
70013	3045.60	2012-04-25	3002	5001

```
SELECT DISTINCT salesman_id  
FROM orders;
```

salesman_id
5006
5002
5001
5005
5003
5007



# Query 3

- Display names and city of salesman, who belongs to the city of Paris.

*salesman(salesman\_id, name, city, commission)*

<u>name</u>	<u>city</u>
Nail Knite	Paris
Mc Lyon	Paris

```
SELECT name,city  
FROM salesman  
WHERE city='Paris';
```

salesman_id	name	city	commission
5001	James Hoog	New York	0.15
5002	Nail Knite	Paris	0.13
5005	Pit Alex	London	0.11
5006	Mc Lyon	Paris	0.14
5003	Lauson Hense		0.12
5007	Paul Adam	Rome	0.13

```
SELECT name,city FROM salesman  
WHERE city='Paris';
```

salesman_id	name	city	commission
5001	James Hoog	New York	0.15
5002	Nail Knite	Paris	0.13
5005	Pit Alex	London	0.11
5006	Mc Lyon	Paris	0.14
5003	Lauson Hense		0.12
5007	Paul Adam	Rome	0.13

# Query 4

- Display all the information for those customers with a grade of 200.

*customer(customer\_id, cust\_name, city, grade, salesman\_id)*

customer_id	cust_name	city	grade	salesman_id
3007	Brad Davis	New York	200	5001
3005	Graham Zusi	California	200	5002
3003	Jozy Altidor	Moscow	200	5007

```
SELECT *  
FROM customer  
WHERE grade = 200;
```

customer_id	cust_name	city	grade	salesman_id
3002	Nick Rimando	New York	100	5001
3005	Graham Zusi	California	200	5002
3004	Fabian Johnson	Paris	300	5006
3007	Brad Davis	New York	200	5001
3009	Geoff Cameron	Berlin	100	5003
3008	Julian Green	London	300	5002
3003	Jozy Altidore	Moscow	200	5007
3001	Brad Guzan	London		5005

```
SELECT * FROM customer  
WHERE grade =200;
```

customer_id	cust_name	city	grade	salesman_id
3002	Nick Rimando	New York	100	5001
3005	Graham Zusi	California	200	5002
3004	Fabian Johnson	Paris	300	5006
3007	Brad Davis	New York	200	5001
3009	Geoff Cameron	Berlin	100	5003
3008	Julian Green	London	300	5002
3003	Jozy Altidore	Moscow	200	5007
3001	Brad Guzan	London		5005

# Query 5

Display the order number, order date and the purchase amount for order(s) which will be delivered by the salesman with ID 5001.

*orders(ord\_no, purch\_amt, ord\_date, customer\_id, salesman\_id)*

ord no	ord date	purch amt
70002	2012-10-05	65.26
70005	2012-07-27	2400.60
70008	2012-09-10	5760.00
70013	2012-04-25	3045.60

```
SELECT ord_no, ord_date, purch_amt
FROM orders
WHERE salesman_id = 5001;
```

ord_no	purch_amt	ord_date	customer_id	salesman_id
70001	150.50	2012-10-05	3005	5002
70009	270.65	2012-09-10	3001	5005
70002	65.26	2012-10-05	3002	5001
70004	110.50	2012-08-17	3009	5003
70007	948.50	2012-09-10	3005	5002
70005	2400.60	2012-07-27	3007	5001
70008	5760.00	2012-09-10	3002	5001
70010	1983.43	2012-10-10	3004	5006
70003	2480.40	2012-10-10	3009	5003
70012	250.45	2012-06-27	3008	5002
70011	75.29	2012-08-17	3003	5007
70013	3045.60	2012-04-25	3002	5001

```
SELECT ord_no, ord_date, purch_amt FROM orders
WHERE salesman_id = 5001;
```

ord_no	ord_date	purch_amt
70001	2012-10-05	150.50
70009	2012-09-10	270.65
70002	2012-10-05	65.26
70004	2012-08-17	110.50
70007	2012-09-10	948.50
70005	2012-07-27	2400.60
70008	2012-09-10	5760.00
70010	2012-10-10	1983.43
70003	2012-10-10	2480.40
70012	2012-06-27	250.45
70011	2012-08-17	75.29
70013	2012-04-25	3045.60

# Query 6

- Show the winner of the 1971 prize for Literature.

*nobel\_win(year, subject, winner, country, category)*

winner  
Pablo Neruda

```
SELECT winner  
FROM nobel_win  
WHERE year = 1971  
AND subject = 'Literature';
```



# Query 7

- Show all the details of the winners with first name Louis.

*nobel\_win(year, subject, winner, country, category)*

year	subject	winner	country	category
1970	Physics	Louis Neel	France	Scientist

```
SELECT *  
FROM nobel_win  
WHERE winner LIKE 'Louis%';
```

# Query 8

- Show all the winners in Physics for 1970 together with the winner of Economics for 1971.

*nobel\_win(year, subject, winner, country, category)*

<u>year</u>	<u>subject</u>	<u>winner</u>	<u>country</u>	<u>category</u>
1970	Physics	Hannes Alfven	Sweden	Scientist
1970	Physics	Louis Neel	France	Scientist
1971	Economics	Simon Kuznets	Russia	Economist

```
SELECT *
FROM nobel_win
WHERE (subject = 'Physics' AND year = 1970)
UNION
(SELECT *
FROM nobel_win
WHERE (subject = 'Economics' AND year = 1971)
);
```

# Query 9

- Show all the winners of Nobel prize in the year 1970 except the subject Physiology and Economics.

*nobel\_win(year, subject, winner, country, category)*

<u>year</u>	<u>subject</u>	<u>winner</u>	<u>country</u>	<u>category</u>
1970	Physics	Hannes Alfvén	Sweden	Scientist
1970	Physics	Louis Néel	France	Scientist
1970	Chemistry	Luis Federico Leloir	France	Scientist
1970	Literature	Aleksandr Solzhenitsyn	Russia	Linguist

```
SELECT *  
FROM nobel_win  
WHERE year = 1970  
AND subject NOT IN ('Physiology','Economics');
```

# Query 10

- Find all the details of the Nobel winners for the subject not started with the letter 'P' and arranged the list as the most recent comes first, then by name in order.

*nobel\_win(year, subject, winner, country, category)*

<u>year</u>	<u>subject</u>	<u>winner</u>	<u>country</u>	<u>category</u>
1994	Literature	Kenzaburo Oe	Japan	Linguist
1994	Economics	Reinhard Selten	Germany	Economist
1987	Chemistry	Donald J. Cram	USA	Scientist
1987	Chemistry	Jean-Marie Lehn	France	Scientist
1987	Literature	Joseph Brodsky	Russia	Linguist
1987	Economics	Robert Solow	USA	Economist
1971	Chemistry	Gerhard Herzberg	Germany	Scientist
1971	Literature	Pablo Neruda	Chile	Linguist
1971	Economics	Simon Kuznets	Russia	Economist
1970	Literature	Aleksandr Solzhenitsyn	Russia	Linguist
1970	Chemistry	Luis Federico Leloir	France	Scientist
1970	Economics	Paul Samuelson	USA	Economist

```
SELECT *  
FROM nobel_win  
WHERE subject NOT LIKE 'P%'  
ORDER BY year DESC, winner;
```

# Query 11

- Find the name and price of the cheapest item(s).

*item\_mast(pro\_id, pro\_name, pro\_price, pro\_com)*

<u>pro_name</u>	<u>pro_price</u>
ZIP drive	250.00
Mouse	250.00

```
SELECT pro_name, pro_price
FROM item_mast
WHERE pro_price = (SELECT MIN(pro_price)
FROM item_mast);
```

# Query 12

- Display all the customers, who are either belongs to the city New York or not had a grade above 100.

*customer(customer\_id, cust\_name, city, grade, salesman\_id)*

<u>customer_id</u>	<u>cust_name</u>	<u>city</u>	<u>grade</u>	<u>salesman_id</u>
3002	Nick Rimando	New York	100	5001
3007	Brad Davis	New York	200	5001
3009	Geoff Cameron	Berlin	100	5003

```
SELECT *  
FROM customer  
WHERE city = 'New York' OR NOT grade > 100;
```

# Query 13

- Find those salesmen with all information who gets the commission within a range of 0.10 and 0.12.

*salesman(salesman\_id, name, city, commission)*

```
SELECT salesman_id, name, city, commission
FROM salesman
WHERE (commission > 0.10 AND commission < 0.12);
```

```
SELECT salesman_id, name, city, commission
FROM salesman
WHERE commission between 0.10 AND 0.12;
```

salesman_id	name	city	commission
5001	James Hoog	New York	0.15
5002	Nail Knite	Paris	0.13
5005	Pit Alex	London	0.11
5006	Mc Lyon	Paris	0.14
5003	Lauson Hense		0.12
5007	Paul Adam	Rome	0.13

```
SELECT salesman_id, name, city, c ommission
FROM salesman
WHERE (commission > 0.10
AND commission < 0.12);
```

salesman_id	name	city	commission
5005	Pit Alex	London	0.11

# Query 14

- Find all those customers with all information whose names are ending with the letter 'n'.

*customer(customer\_id, cust\_name, city, grade, salesman\_id)*

```
SELECT *  
FROM customer  
WHERE cust_name LIKE '%n';
```

customer_id	cust_name	city	grade	salesman_id
3002	Nick Rimando	New York	100	5001
3005	Graham Zusi	California	200	5002
3004	Fabian Johnson	Paris	300	5006
3007	Brad Davis	New York	200	5001
3009	Geoff Cameron	Berlin	100	5003
3008	Julian Green	London	300	5002
3003	Jozy Altidore	Moscow	200	5007
3001	Brad Guzan	London		5005

```
SELECT *  
FROM customer  
WHERE cust_name LIKE '%n';
```

customer_id	cust_name	city	grade	salesman_id
3004	Fabian Johnson	Paris	300	5006
3009	Geoff Cameron	Berlin	100	5003
3008	Julian Green	London	300	5002
3001	Brad Guzan	London		5005



# Query 15

- Find those salesmen with all information whose name containing the 1st character is 'N' and the 4th character is 'l' and rests may be any character.

*salesman(salesman\_id, name, city, commission)*

```
SELECT *  
FROM salesman  
WHERE name LIKE 'N__l%';
```

salesman_id	name	city	commission
5001	James Hoog	New York	0.15
5002	Nail Knite	Paris	0.13
5005	Pit Alex	London	0.11
5006	Mc Lyon	Paris	0.14
5003	Lauson Hense		0.12
5007	Paul Adam	Rome	0.13

```
SELECT *  
FROM salesman  
WHERE name LIKE 'N__l%';
```

salesman_id	name	city	commission
5002	Nail Knite	Paris	0.13

# Query 16

- Find that customer with all information who does not get any grade except NULL.

*customer(customer\_id, cust\_name, city, grade, salesman\_id)*

```
SELECT *  
FROM customer  
WHERE grade IS NULL;
```

customer_id	cust_name	city	grade	salesman_id
3002	Nick Rimando	New York	100	5001
3005	Graham Zusi	California	200	5002
3004	Fabian Johnson	Paris	300	5006
3007	Brad Davis	New York	200	5001
3009	Geoff Cameron	Berlin	100	5003
3008	Julian Green	London	300	5002
3003	Jozy Altidore	Moscow	200	5007
3001	Brad Guzan	London		5005

```
SELECT *  
FROM customer  
WHERE grade IS NULL ;
```

customer_id	cust_name	city	grade	salesman_id
3001	Brad Guzan	London		5005

# Query 17

- Find the total purchase amount of all orders.

*orders(ord\_no, purch\_amt, ord\_date, customer\_id, salesman\_id)*

```
SELECT SUM (purch_amt)  
FROM orders;
```

ord_no	purch_amt	ord_date	customer_id	salesman_id
70001	150.50	2012-10-05	3005	5002
70009	270.65	2012-09-10	3001	5005
70002	65.26	2012-10-05	3002	5001
70004	110.50	2012-08-17	3009	5003
70007	948.50	2012-09-10	3005	5002
70005	2400.60	2012-07-27	3007	5001
70008	5760.00	2012-09-10	3002	5001
70010	1983.43	2012-10-10	3004	5006
70003	2480.40	2012-10-10	3009	5003
70012	250.45	2012-06-27	3008	5002
70011	75.29	2012-08-17	3003	5007
70013	3045.60	2012-04-25	3002	5001

```
SELECT SUM (purch_amt)  
FROM orders ;
```

purch_amt
150.50
270.65
65.26
110.50
948.50
2400.60
5760.00
1983.43
2480.40
250.45
75.29
3045.60

Sum : 17541.18

# Query 18

- Find the number of salesman currently listing for all of their customers.

*orders(ord\_no, purch\_amt, ord\_date, customer\_id, salesman\_id)*

```
SELECT COUNT (salesman_id)  
FROM orders;
```

```
SELECT COUNT (DISTINCT salesman_id)  
FROM orders;
```

ord_no	purch_amt	ord_date	customer_id	salesman_id
70001	150.50	2012-10-05	3005	5002
70009	270.65	2012-09-10	3001	5005
70002	65.26	2012-10-05	3002	5001
70004	110.50	2012-08-17	3009	5003
70007	948.50	2012-09-10	3005	5002
70005	2400.60	2012-07-27	3007	5001
70008	5760.00	2012-09-10	3002	5001
70010	1983.43	2012-10-10	3004	5006
70003	2480.40	2012-10-10	3009	5003
70012	250.45	2012-06-27	3008	5002
70011	75.29	2012-08-17	3003	5007
70013	3045.60	2012-04-25	3002	5001

```
SELECT COUNT (DISTINCT salesman_id)  
FROM orders;
```

salesman_id
5002
5005
5001
5003
5006
5007

Count : 6

# Query 19

- Write a SQL statement that counts all orders for a date August 17th, 2012.

*orders(ord\_no, purch\_amt, ord\_date, customer\_id, salesman\_id)*

```
SELECT COUNT(*)  
FROM orders  
WHERE ord_date = '2012-08-17';
```

ord_no	purch_amt	ord_date	customer_id	salesman_id
70001	150.50	2012-10-05	3005	5002
70009	270.65	2012-09-10	3001	5005
70002	65.26	2012-10-05	3002	5001
70004	110.50	2012-08-17	3009	5003
70007	948.50	2012-09-10	3005	5002
70005	2400.60	2012-07-27	3007	5001
70008	5760.00	2012-09-10	3002	5001
70010	1983.43	2012-10-10	3004	5006
70003	2480.40	2012-10-10	3009	5003
70012	250.45	2012-06-27	3008	5002
70011	75.29	2012-08-17	3003	5007
70013	3045.60	2012-04-25	3002	5001

```
SELECT COUNT(*)  
FROM orders  
WHERE ord_date='2012-08-17';
```

WHERE ord\_date='2012-08-17'

ord_no	purch_amt	ord_date	customer_id	salesma
70004	110.50	2012-08-17	3009	5003
70011	75.29	2012-08-17	3003	5007

count
2

# Query 20

- Find the highest grade for each of the cities of the customers.

*customer(customer\_id, cust\_name, city, grade, salesman\_id)*

customer_id	cust_name	city	grade	salesman_id
3002	Nick Rimando	New York	100	5001
3005	Graham Zusi	California	200	5002
3004	Fabian Johnson	Paris	300	5006
3007	Brad Davis	New York	200	5001
3009	Geoff Cameron	Berlin	100	5003
3008	Julian Green	London	300	5002
3003	Jozy Altidore	Moscow	200	5007
3001	Brad Guzan	London		5005

```
SELECT city, MAX(grade)
FROM customer
GROUP BY city ;
```

```
SELECT city, MAX(grade)
FROM customer
GROUP BY city;
```

city	grade
New York	100
California	200
Paris	300
New York	200
Berlin	100
London	300
Moscow	200
London	

city	max
California	200
Moscow	200
Paris	300
London	300
Berlin	100
New York	200

# Query 21

- Find the highest purchase amount ordered by each customer with their ID and highest purchase amount.

*orders(ord\_no, purch\_amt, ord\_date, customer\_id, salesman\_id)*

```
SELECT customer_id, MAX(purch_amt)
FROM orders
GROUP BY customer_id;
```

ord_no	purch_amt	ord_date	customer_id	salesman_id
70001	150.50	2012-10-05	3005	5002
70009	270.65	2012-09-10	3001	5005
70002	65.26	2012-10-05	3002	5001
70004	110.50	2012-08-17	3009	5003
70007	948.50	2012-09-10	3005	5002
70005	2400.60	2012-07-27	3007	5001
70008	5760.00	2012-09-10	3002	5001
70010	1983.43	2012-10-10	3004	5006
70003	2480.40	2012-10-10	3009	5003
70012	250.45	2012-06-27	3008	5002
70011	75.29	2012-08-17	3003	5007
70013	3045.60	2012-04-25	3002	5001

```
SELECT customer_id, MAX(purch_amt)
FROM orders
GROUP BY customer_id ;
```

customer_id	purch_amt
3005	150.5
3001	270.65
3002	65.26
3009	110.5
3005	948.5
3007	2400.6
3002	5760
3004	1983.43
3009	2480.4
3008	250.45
3003	75.29
3002	3045.6

customer_id	max
3004	1983.43
3008	250.45
3001	270.65
3007	2400.6
3005	948.5
3002	5760
3009	2480.4
3003	75.29

# Query 22

- Find the highest purchase amount ordered by each customer on a particular date with their ID, order date and highest purchase amount.

*orders(ord\_no, purch\_amt, ord\_date, customer\_id, salesman\_id)*

ord_no	purch_amt	ord_date	customer_id	salesman_id
70001	150.50	2012-10-05	3005	5002
70009	270.65	2012-09-10	3001	5005
70002	65.26	2012-10-05	3002	5001
70004	110.50	2012-08-17	3009	5003
70007	948.50	2012-09-10	3005	5002
70005	2400.60	2012-07-27	3007	5001
70008	5760.00	2012-09-10	3002	5001
70010	1983.43	2012-10-10	3004	5006
70003	2480.40	2012-10-10	3009	5003
70012	250.45	2012-06-27	3008	5002
70011	75.29	2012-08-17	3003	5007
70013	3045.60	2012-04-25	3002	5001

```
SELECT customer_id, ord_date, MAX( purch_amt )  
FROM orders  
GROUP BY customer_id, ord_date;
```

```
SELECT customer_id, ord_date, MAX(purch_amt)  
FROM orders  
GROUP BY customer_id, ord_date;
```

customer_id	ord_date	max
3009	2012-10-10	2480.4
3007	2012-07-27	2400.6
3005	2012-09-10	948.5
3002	2012-09-10	5760
3002	2012-04-25	3045.6
3001	2012-09-10	270.65
3004	2012-10-10	1983.43
3003	2012-08-17	75.29
3005	2012-10-05	150.5
3008	2012-06-27	250.45
3002	2012-10-05	65.26
3009	2012-08-17	110.5



# Query 23

- Find the highest purchase amount on a date '2012-08-17' for each salesman with their ID.

*orders(ord\_no, purch\_amt, ord\_date, customer\_id, salesman\_id)*

```
SELECT salesman_id, MAX(purch_amt)
FROM orders
WHERE ord_date = '2012-08-17'
GROUP BY salesman_id;
```

ord_no	purch_amt	ord_date	customer_i	salesma
70001	150.50	2012-10-05	3005	5002
70009	270.65	2012-09-10	3001	5005
70002	65.26	2012-10-05	3002	5001
70004	110.50	2012-08-17	3009	5003
70007	948.50	2012-09-10	3005	5002
70005	2400.60	2012-07-27	3007	5001
70008	5760.00	2012-09-10	3002	5001
70010	1983.43	2012-10-10	3004	5006
70003	2480.40	2012-10-10	3009	5003
70012	250.45	2012-06-27	3008	5002
70011	75.29	2012-08-17	3003	5007
70013	3045.60	2012-04-25	3002	5001

```
SELECT salesman_id, MAX(purch_amt)
FROM orders
WHERE ord_date = '2012-08-17'
GROUP BY salesman_id;
```

WHERE ord\_date = '2012-08-17'

GROUP BY salesman\_id

ord_no	purch_amt	ord_date	customer_i	salesma
70004	110.50	2012-08-17	3009	5003
70011	75.29	2012-08-17	3003	5007

salesman_id	max
5003	110.50
5007	75.29

# Query 24

- Find the highest purchase amount with their customer ID and order date, for only those customers who have the highest purchase amount in a day is more than 2000.

*orders(ord\_no, purch\_amt, ord\_date, customer\_id, salesman\_id)*

```
SELECT customer_id, ord_date, MAX(purch_amt)
FROM orders
GROUP BY customer_id, ord_date
HAVING MAX(purch_amt) > 2000.00;
```

